

# LVL CY200

## TECHNICAL SPECIFICATIONS



[www.ElevatorandLifts.com](http://www.ElevatorandLifts.com)

**LEVEL**  
**UP**  
ELEVATOR & LIFTS

## OVERVIEW

### General Description

Elevate your home with the LVL CY200, a sleek and modern solution for two passengers. Featuring a winding drum conveyance system and a fully panoramic cabin, it provides stunning views while maintaining a modern look. Manufactured using an aluminum frame and polycarbonate panels, the self-supported, free-standing design for these home elevators eliminates the need for a shaft or pit, making installation straightforward. Compliant with ASME A17.1 safety standards, the LVL CY200 seamlessly blends advanced technology with elegant style, enhancing both functionality and the visual appeal of your living space.

## COLORS



Black




Silver



Gray



Taupe



White

Custom Colors Available with RAL Provided

## MECHANICAL / ELECTRICAL

220V - 240V / 5A / Single Phase - 110v Lighting Circuit

1.1 kW Worm Geared Motors

1/4" 7x19 Galvanized Steel Cables

Dual Winding Drums

Single-Disc Spring Setting Brake

## CABIN

Cabin Entrance Width 23.5" (597mm)

Internal Cabin Height 79" (2007mm)

Internal Cabin Diameter 32" (813mm)

Automatic LED Lighting and Cabin Fan

24V Electrical Circuits Inside Cabin

## CYLINDER

External Cylinder Diameter 37.75" (959mm)

Bottom Floor Cylinder Height 92" (2337mm)

Rated Load 500lb (227kg)

Speed 32 fpm

Minimum Floor to Floor Height 93.5" (2375mm)

Minimum Floor to Ceiling Height 81" (2057mm)

Minimum Overhead 105" (2667mm)

Door Height 77" (1956mm)

Door Height with Closer 79" (2007mm)

Through-Floor Opening Size 40" (1016mm)

Pit or Hoistway Required? NO

Installation Entry Access Required 40" (1016mm)

Single Push Call Buttons / Travel Up to 4 Stops or 38ft of Rise

## SAFETY

Power Failure UPS Battery Backup System

Manual Lowering Device

Mechanical Emergency Safeties

Electric Interlocks at Each Landing

Alarm System and Telephone Inside Cabin

